

C:\Cam Pro Plus\CPP\CACÁ DAUD\COMANDO EDER SETI NOVO.CPP

|                 |             | LIFT    | DUR.   | OPEN            | CLOSE      | AREA   |
|-----------------|-------------|---------|--------|-----------------|------------|--------|
| Lobe            | I1          | ----    | ----   | -----           | -----      | -----  |
| Centerline      | 113,72 BTDC | 0,15    | 288,37 | 78,11 BBDC      | 30,26 ATDC | 1300,5 |
| .050 Lift C/L   | 113,14 BTDC | 0,51    | 276,25 | 71,33 BBDC      | 24,92 ATDC | 1298,9 |
| Runout          | 0,0127      | 1,27    | 263,43 | 64,84 BBDC      | 18,60 ATDC | 1293,3 |
| Peak Open Acc.  | 0,03720     | 2,54    | 246,27 | 56,20 BBDC      | 10,07 ATDC | 1274,5 |
| Peak Nose Acc.  | -0,00876    | 3,81    | 230,27 | 48,17 BBDC      | 2,10 ATDC  | 1247,8 |
| Peak Close Acc. | 0,03599     | 5,08    | 214,28 | 40,14 BBDC      | 5,86 BTDC  | 1211,0 |
| Lift @ TDC      | 4,144       | 6,35    | 197,95 | 31,95 BBDC      | 14,00 BTDC | 1169,5 |
| Valve Lash      | 0,250       | 7,62    | 181,20 | 23,58 BBDC      | 22,38 BTDC | 1111,0 |
| Lobe Separation | 113,7       | 8,89    | 163,44 | 14,68 BBDC      | 31,24 BTDC | 1037,6 |
|                 |             | 10,16   | 143,84 | 4,87 BBDC       | 41,03 BTDC | 944,1  |
|                 |             | 11,43   | 121,61 | 6,26 ABDC       | 52,13 BTDC | 824,0  |
|                 |             | 12,70   | 94,64  | 19,72 ABDC      | 65,64 BTDC | 661,0  |
|                 |             | 14,8093 | ---    | PEAK CAM LIFT   | ---        |        |
|                 |             | 14,5593 | ---    | PEAK VALVE LIFT | ---        |        |

C:\Cam Pro Plus\CPP\CACÁ DAUD\COMANDO EDER SETI NOVO.CPP

|                 |             | LIFT    | DUR.   | OPEN            | CLOSE      | AREA   |
|-----------------|-------------|---------|--------|-----------------|------------|--------|
| Lobe            | E1          | ----    | ----   | -----           | -----      | -----  |
| Centerline      | 113,72 ATDC | 0,15    | 292,46 | 31,96 BTDC      | 80,51 ABDC | 1339,4 |
| .050 Lift C/L   | 114,50 ATDC | 0,51    | 282,92 | 27,03 BTDC      | 75,89 ABDC | 1338,0 |
| Runout          | 0,0330      | 1,27    | 270,89 | 20,87 BTDC      | 70,02 ABDC | 1331,6 |
| Peak Open Acc.  | 0,03729     | 2,54    | 254,43 | 12,62 BTDC      | 61,80 ABDC | 1317,2 |
| Peak Nose Acc.  | -0,00752    | 3,81    | 238,46 | 4,61 BTDC       | 53,86 ABDC | 1291,9 |
| Peak Close Acc. | 0,03905     | 5,08    | 222,19 | 3,54 ATDC       | 45,73 ABDC | 1250,5 |
| Lift @ TDC      | 4,532       | 6,35    | 205,28 | 11,98 ATDC      | 37,26 ABDC | 1200,9 |
| Valve Lash      | 0,300       | 7,62    | 187,58 | 20,88 ATDC      | 28,45 ABDC | 1137,8 |
| Lobe Separation | 113,7       | 8,89    | 168,70 | 30,32 ATDC      | 19,02 ABDC | 1058,5 |
|                 |             | 10,16   | 148,12 | 40,61 ATDC      | 8,74 ABDC  | 959,2  |
|                 |             | 11,43   | 125,02 | 52,14 ATDC      | 2,84 BBDC  | 833,0  |
|                 |             | 12,70   | 96,93  | 66,17 ATDC      | 16,90 BBDC | 661,9  |
|                 |             | 14,7850 | ---    | PEAK CAM LIFT   | ---        |        |
|                 |             | 14,4850 | ---    | PEAK VALVE LIFT | ---        |        |

C:\Cam Pro Plus\CPP\CACÁ DAUD\COMANDO EMCDR 8V.CPP

|                 |             | LIFT    | DUR.   | OPEN            | CLOSE      | AREA   |
|-----------------|-------------|---------|--------|-----------------|------------|--------|
| Lobe            | I1          | ----    | ----   | -----           | -----      | -----  |
| Centerline      | 113,94 BTDC | 0,15    | 315,39 | 93,25 BBDC      | 42,14 ATDC | 1196,5 |
| .050 Lift C/L   | 113,01 BTDC | 0,51    | 291,79 | 79,60 BBDC      | 32,19 ATDC | 1193,0 |
| Runout          | 0,0127      | 1,27    | 268,10 | 66,89 BBDC      | 21,21 ATDC | 1182,8 |
| Peak Open Acc.  | 0,01301     | 2,54    | 243,07 | 54,07 BBDC      | 9,00 ATDC  | 1159,5 |
| Peak Nose Acc.  | -0,00859    | 3,81    | 223,16 | 44,05 BBDC      | 0,89 BTDC  | 1128,0 |
| Peak Close Acc. | 0,01352     | 5,08    | 204,63 | 34,75 BBDC      | 10,12 BTDC | 1086,8 |
| Lift @ TDC      | 3,690       | 6,35    | 186,12 | 25,52 BBDC      | 19,39 BTDC | 1033,9 |
| Valve Lash      | 0,250       | 7,62    | 166,97 | 16,01 BBDC      | 29,05 BTDC | 967,0  |
| Lobe Separation | 113,9       | 8,89    | 146,42 | 5,75 BBDC       | 39,34 BTDC | 882,1  |
|                 |             | 10,16   | 123,88 | 5,42 ABDC       | 50,71 BTDC | 774,6  |
|                 |             | 11,43   | 98,34  | 17,75 ABDC      | 63,91 BTDC | 625,1  |
|                 |             | 12,70   | 65,09  | 33,83 ABDC      | 81,09 BTDC | 435,3  |
|                 |             | 13,9643 | ---    | PEAK CAM LIFT   | ---        |        |
|                 |             | 13,7143 | ---    | PEAK VALVE LIFT | ---        |        |

C:\Cam Pro Plus\CPP\CACÁ DAUD\COMANDO EMCDR 8V.CPP

|                 |             | LIFT    | DUR.   | OPEN            | CLOSE      | AREA   |
|-----------------|-------------|---------|--------|-----------------|------------|--------|
| Lobe            | E1          |         |        |                 |            |        |
| Centerline      | 113,94 ATDC | 0,15    | 305,02 | 39,37 BTDC      | 85,65 ABDC | 1186,6 |
| .050 Lift C/L   | 114,61 ATDC | 0,51    | 287,35 | 29,54 BTDC      | 77,81 ABDC | 1183,5 |
| Runout          | 0,0305      | 1,27    | 265,57 | 18,09 BTDC      | 67,47 ABDC | 1173,4 |
| Peak Open Acc.  | 0,01303     | 2,54    | 241,54 | 5,84 BTDC       | 55,69 ABDC | 1149,6 |
| Peak Nose Acc.  | -0,00831    | 3,81    | 221,87 | 3,99 ATDC       | 45,85 ABDC | 1117,2 |
| Peak Close Acc. | 0,01316     | 5,08    | 203,38 | 13,31 ATDC      | 36,68 ABDC | 1075,0 |
| Lift @ TDC      | 3,276       | 6,35    | 184,88 | 22,54 ATDC      | 27,42 ABDC | 1020,7 |
| Valve Lash      | 0,300       | 7,62    | 165,71 | 32,12 ATDC      | 17,83 ABDC | 952,5  |
| Lobe Separation | 113,9       | 8,89    | 145,29 | 42,30 ATDC      | 7,59 ABDC  | 866,8  |
|                 |             | 10,16   | 122,82 | 53,55 ATDC      | 3,63 BBDC  | 758,6  |
|                 |             | 11,43   | 97,39  | 65,96 ATDC      | 16,65 BBDC | 619,7  |
|                 |             | 12,70   | 64,85  | 81,80 ATDC      | 33,35 BBDC | 421,6  |
|                 |             | 14,0445 | ---    | PEAK CAM LIFT   | ---        |        |
|                 |             | 13,7445 | ---    | PEAK VALVE LIFT | ---        |        |

DADOS DO COMANDO COMPARATIVO